
### Panasonic.

# BT-111390Y

## 13" Diagonal High-Grade Color Video Monitor



#### **Features**

- High Resolution- 750 Lines
- On- Screen Menus for simple set-up
- Memory Recall from menu
- Control Lock

- EBU Phosphor for improved clarity
- User Selectable Aspect Ratios
- CPU Controled picture stability
- User Selectable Color Temperatures



#### BT-H1390Y 13" Diagonal High-Grade Color Video Monitor

#### **Specifications:**

Video Inputs

Type : High Resolution Color Monitor RGB Con't.: R: 0.7 V p-p, 75Ω

Color systems: NTSC 3.58 MHz, Netec 4.43 MHz, PALB: 0.7 V p-p,  $75\Omega$ Picture tube: 13'' (33cm) diagonally measured,G: 0.7 V p-p,  $75\Omega$ 

trio-dot type (dot pitch of 0.28 mm), G on sync:1.0 V p-p, 75Ω negative sync

EBU phosphor Component: R-Y, B-Y component

Scanning frequency: H: 15.734 kHz (NTSC 3.58/4.43MHz) RGB/COMPO (SDI)

15.625 kHz (PAL) (1 line: common with analog RGB)

V. 59.94 Hz (NTSC 3.58/4 13 MHz)

Y: 1.0 V p-p, 75Ω negative sync

50 Hz (PAL) R-Y: 0.7 V p-p, 75Ω Horizontal resolution : 750 TV lines or more B-Y: 0.7 V p-p,  $75\Omega$ 

Color temperature : 6500°K; x=0.313, y=0.329 Termination Switch Provided

9300°K; x=0.283, y=0.297 External sync Inputs: Composite SYNC (1 line) 1.0-4.0 V p-p

(selectable) BNC x 2 (with 1 bridge-connected

: Composite video output)

1 & 2: INPUT A,B (2 lines). BNC x 2 each Audio Inputs: AUDIO A,B, RGB/COMPO(SDI)

(with bridge-connected output) (3 lines). RCA x 2 each

Termination switches provided (with 1 bridge-connected output)

1.0 v p-p,  $75\Omega$  negative sync Tally/remote: DIN (8-pin) x1

3; Y/C (1 line). DIN (4-pin) x2 Audio power output: .8 W

(with 1 bridge-connected output)

Built-in speaker: 9 cm x 5 cm OVAL x 1

Termination switch provided

Operation temperature:0-40"C (20-60% RH)

RGB: 1.0 v p-p, 75Ω negative sync Power requirements: 120 V AC, 60/60 Hz

RGB (1 line: common with Y, R-Y, B-Y Power consumption: .46 A

component), Dimensions (WxHxD):13-23/32" x 13-21/32" x 15-15/32"

BNC x 6 (with 3 bridge-connected (348 mm x 355 mm x 393 mm)

output) Power consumption: 35.6 lbs (16.2 kg)

Termination switches provided Provided accessory: Power cord x1

Weights and dimensions shown are approximate. Specifications and product design are subject to change without notice. This product may be subject to export control regulations.



Broadcast a relevision cyclemo company

EASTERN: One Panasonic Way, Secaucus, NJ 07094 (201) 348-7410

**SOUTHERN:** 1225 Northbrook Parkway 1-160, Suwanee, GA 30024 (770) 338-6835 **WESTERN:** 4001 W. Alameda Ave., Suite 100, Burbank, CA 91505 (818) 562-1501