



BY BOUNDLESS TECHNOLOGIES

## ADD5 4000/260 Video Display Terminal

Wyse 50, 50+ and 60 VDT  
emulation set

Best UNIX compatibility  
and Video performance in a  
14" monochrome Terminal

High reliability backed by  
our 3 year warranty

Designed and manufactured  
in the USA



The ADD5 4000/260 has advanced data access, data manipulation and display features, including cut and paste and dual host/dual session capabilities. The terminal features selectable refresh rates up to 100Hz for clear, flicker free viewing and an ISO 9241.3 compliant mode to reduce operator eye strain. Bezel to bezel over scan is also available up to 82 Hz.

The ADD5 4000/260 emulation set includes the Wyse WY-50/50+, WY-60, DEC VT-100, VT-220, VT 320 and the ADD5 Viewpoint and PC-Term. The ADD5 4000/260 is an ideal solution for customers using Wyse display terminals in legacy applications. As a SCO developer, you can count on the ADD5 4000/260 to function properly in the SCO environment.

Built in the Boundless "JIT" manufacturing facility on Long Island allows rapid delivery of any terminal in any configuration. You can select the ADD5 4000/260 of your choice in any phosphor color with any keyboard with the assurance that your order will be delivered quickly. Boundless backs its ADD5 4000/260 with a money back guarantee and a 3 year warranty.

**Boundless Technologies 1-800-231-5445**



BY BOUNDLESS TECHNOLOGIES

## ADD5 4000/260 Video Display Terminal

### Display Features:

- ◇ 14" Flat face, reduced glare, high resolution screen
- ◇ Bezel to Bezel overscan
- ◇ 60, 71, 82 and 100 hz selectable refresh rates for clear flicker free viewing
- ◇ Choice of Green, Amber or White phosphor
- ◇ 26,30, or 52 lines with top and/or bottom status lines
- ◇ 80 or 132 columns
- ◇ 10 pages of memory
- ◇ Variable-speed smooth scroll
- ◇ Double high, double wide characters
- ◇ Selectable screen saver

### Desk Accessories:

- ◇ Calculator
- ◇ Calendar
- ◇ Clock
- ◇ ASCII Chart

### Communications:

- ◇ Full/half duplex
- ◇ Local block
- ◇ Monitor mode
- ◇ Serial host Port
  - RS-232C main host
  - DTE, DB 25 female
  - up to 134.4k baud
- ◇ Serial Auxiliary Port
  - RS-232C second host/aux serial port
  - DCE, DB 25 female
  - Up to 38.4k baud
- ◇ Parallel Printer Port
  - IBM PC and Centronic compatible
- ◇ Optional Ethernet
  - 10BaseT TCP/IP
- ◇ Optional current loop

### Dual Host Support

- ◇ Simultaneous connection and operation with two hosts
- ◇ Flexible display formats
- ◇ "Hot key" to alternate between hosts
- ◇ Printer port support for both hosts

### Terminal Emulations:

- ◇ ADD5 Viewpoint
- ◇ VT 100
- ◇ VT 220
- ◇ VT 320
- ◇ Wyse 50
- ◇ Wyse 50+
- ◇ Wyse 60
- ◇ TVI 925
- ◇ SCO Console
- ◇ BBS ANSI
- ◇ AT 386

### Regulatory Agencies:

- ◇ UL
- ◇ TUV-GS Mark
- ◇ FCC-B,
- ◇ CE
- ◇ MRP-II
- ◇ DHHS
- ◇ VCCI
- ◇ EPA Energy Star
- ◇ ISO 92413
- ◇ VCCI
- ◇ EN 55022 Class B
- ◇ VFG 243 B

### Power:

- ◇ 90-264 Vac, 47-63 hz
- ◇ .20-.50a (max) operating
- ◇ EPA Energy Star ® "Sleep Mode"

### Physical Characteristics

- ◇ L: 13.0", 33 cm
- ◇ W: 12.5", 31.8 cm
- ◇ H: 13.4", 34 cm
- ◇ Shipping weight: 29 lbs. , 13.2 kg

Boundless Technologies  
1916 Route 96  
Phelps, NY 14532  
Phone (toll-free): 1-800-231-5445  
Phone: 1-315-548-6189  
Fax: 1-315-548-5100  
[www.BoundlessTerminals.com](http://www.BoundlessTerminals.com)